



TM-T82X

FLEXIBILITY AND RELIABILITY AT YOUR FINGERTIPS.

Enjoy the power of reliability and flexibility in your business with the cost effective TM-T82X. Printing at a high speed of 200 mm/sec,[^] the easy-to configure printer supports USB, Ethernet, and RS-232, and can be placed anywhere thanks to its compact and durable body. A perfect companion for small business owners.



Compact



Print



Auto-Cutter



Cost-Effective



Built-in Power Supply

Unrivalled Performance

With a MCBF of 60 million lines and an auto-cutter life of 1.5 million cuts[^].

Ease-of-use

Features drop-in paper loading, auto-cutter and status LEDs.

Adaptive Design

Space-saving compact design makes it easy to suit even the most demanding retail environments.

[^]Under standard test conditions.

SPECIFICATIONS

TM-T82X

EPSON
EXCEED YOUR VISION

MODEL NUMBER	TM-T82X
Printing Method	Thermal line printing
Print Font	
Font	9 x 17 / 12 x 24, Hanji Font: 24 x 24, Thai Font: 9 x 24 / 12 x 24
Character Size (W x H)	0.88 x 2.13 mm / 1.25 x 3 mm, Hanji font: 3 x 3 mm, Thai font: 0.88 x 3 mm / 1.25 x 3 mm
Character Set	95 Alphanumeric, 18-set International, 128 x 43 pages (including Thai / Viet and user-defined page) Hanzi: Simplified Chinese: GB18030-2000: 28,553 Barcode: UPC-A, UPC-E, JAN13 (EAN13), JAN8 (EAN), CODE39, ITF, CODABAR (NW-7), CODE93, CODE128, GS1-128, GS1 DataBar Two-dimensional code: PDF417, QR Code, MaxiCode, 2D GS1 DataBar, Composite Symbology
Characters Per Inch	22.6 cpi / 16.9 cpi, Hanji Font: 7.8 cpi, Thai Font: 22.6 cpi / 16.9 cpi
Interface	TM-T82X-461: USB + Serial TM-T82X-462: Network
Receive Data Buffer	4 KB or 45 bytes
Print Speed	Max 200 mm/sec
Dot Density	203 x 203 dpi
Paper	
Roll Paper Width and Roll Diameter	79.5 ± 0.5 mm
Power	
Supply Voltage	AC 100 to 230 V / 50 to 60 Hz
Power Consumption	
Operating	Approx. 27.8 W
Standby	Approx 0.96 W
Power Supply	Built-in power supply
Reliability	
Printer Mechanism Life	15 million lines
Auto Cutter Life	1.5 million cuts
MTBF	360,000 hours
MCBF	60,000,000 lines
Overall Dimensions (W x D x H)	149 x 192 x 140 mm
Mass	Approx. 1.5 kg
Standard Accessories ROM	Roll paper x 1 roll (for checking the initial movement of the printer), Setup guide, USB cable for USB + Serial model
Installation	Horizontally
Driver Supported OS	Windows, Mac, Linux
Driver Features	True font replacement
Built-in Feature	Automatic Paper Reduction, Automatic paper cut with logo printing, QR Code Quick Pairing (for Ethernet Model only)

Dimensions & Weight

Weight: Approx. 1.5 kg (3.31 lbs)



Legend

dpi dots per 25.4 mm (dots per inch)
cpi characters per 25.4 mm
(characters per inch)

© 2020 Epson India Pvt. Ltd. All Rights Reserved
Reproduction in part or in whole, without the written permission from Epson, is strictly prohibited
EPSON and EXCEED YOUR VISION are registered trademarks of Seiko Epson Corporation. All other products names and other company names used herein are for identification purposes only and are the trademarks or registered trademarks of their respective owners. Epson disclaims any and all rights in those marks. Print samples shown are simulations only. Specifications and product availability are subject to change without notice and may vary between countries. Please check with local Epson offices for more information.

Apple, iPad and iPhone are trademarks of Apple Inc., registered in the U.S. and other countries. App Store is a service mark of Apple Inc.

Android is a trademark of Google Inc.

Information correct as at July 2020.

EPSON INDIA PVT. LTD.

12th Floor, The Millenia, Tower A, No.1,
Murphy Road, Ulsoor, Bangalore - 560 008
Tel: 080-4566 5000 Fax: 080-4566 5005

Regional Offices:

Ahmedabad - 3314 8500/01, Chennai - 3967 7500, Cochin - 4012 315,
Coimbatore - 98942 19200, Hyderabad - 4857 0032, Jaipur - 78699 11699, Kolkata - 4603 4729,
Mumbai - 3079 8200, New Delhi - 3312 0300, Pune - 3028 6000/05



Epson Helpline: For product info or service - 1800 425 0011
For service - 1800 123 001 600 (9AM - 6PM) (Mon - Sat)
Email: pos@eid.epson.co.in

www.epson.co.in

Dealer's Stamp